



**Hot Crack Filler**  
**Product Data Sheet**

**Description**

A highly modified asphalt crack sealant ideally suited for use on California streets and highways where heavy traffic is a concern. This Parking lot Type 1 crack sealant is highly modified which results in high stiffness and flexural properties. Ingredients include asphalt and modifiers, including virgin synthetic and reclaimed rubber. Recommended for use by public and private agencies where a firm, yet pliable, fast curing material is required. This cold applied sealant is pliable, firm and fast curing.

**SPECIFICATIONS:** Meets California requirements. ASTM testing detailed below.

**SURFACE PREPARATION:** Prior to use the applicator must read and follow installation instructions for hot applied crack fillers and sealers. All safety precautions must be followed as outlined by OSHA and GHS.

**APPLICATION:** Our Crack filler is supplied in a 30# box.

<b>Min. Heating temperature</b>	<b>380F</b>
<b>Max. Application temperature</b>	<b>400F</b>

**WARNING!** HARMFUL OR FATAL IF SWALLOWED. FOR EXTERIOR USE ONLY. KEEP OUT OF REACH OF CHILDREN.

**Typical Properties:**

<b>PROPERTY</b>	<b>METHOD</b>	<b>TYPICAL RESULT</b>
Penetration @ 77F	ASTM D5/T59	25 dmm
Penetration @ 115F	ASTM D5/T59	70 max
Softening Point	ASTM D36	210-220 F
Ductility @ 77F	ASTM D113	30 min.
Resilience	ASTM D5329	50% min.
Flexibility @ 0F	In- house	Pass
Tensile Adhesion	ASTM D5329	>500%
Asphalt Compatibility	ASTM D5329	Pass

**WARRANTY AND DISCLAIMER:** This product is believed to be of good quality and to be in accordance with the specifications set forth herein. If the product proves to be defective, it shall be replaced at the cost of Advantage. Such replacement is and shall be the only liability of Advantage. Advantage is not liable for product failure where poor drainage and ponding water exist. Advantage shall not be responsible to the consumer or any person for labor costs of any kind or any other costs or damages associated with the product or its installation, application or reapplication or any damages resulting therefrom. This warranty is exclusive and there are no other warranties either expressed or implied, including warranties of fitness or merchantability. No other written or oral representation by any person, entity, dealer, installer or representative of Advantage shall have any force or effect. For additional warranty and disclaimer information, contact the Advantage corporate office at [www.Advantagesealing.com](http://www.Advantagesealing.com).