



PermaFast
Product Data Sheet

Description

Permafast Sealcoat Additive is specifically formulated from unique base stocks and pigments, designed to protect, enhance, and speed up drying time to anionic base sealcoats with ease of mixing on field in mind. It contains no coal-tar and remains environmentally friendly. Permafast is engineered with a high resin content to make your sealcoat tougher and longer lasting and laid down faster speeding up coats between jobs.

SPECIFICATIONS: Meets requirements for ASTM D217, D3910, AASHTO T-4556, Federal Spec TT_C_555B

SURFACE PREPARATION:

Material Preparation:

- If material is in an agitated tank, add a ratio of minimum dose 5 gallons per 1000 gallons of sealcoat and mix thoroughly with agitator. Dose can be increased for faster dry times.
- If material is in buckets, add a ratio of 4oz per bucket and mix with a handheld drill and standard ribbon blade mixer attachment.
- If material is in 250 gal. totes, add a ratio of 1 and a half gallons and mix using a tote mixer or handheld drill with ribbon blade attachment.

Typical Properties:

Test Methods	Minimum	Maximum	AVG.
Viscosity KU	N/A	N/A	80
PH	6	9	8.1
Appearance	REPORT	REPORT	Light grey to black
Typical Density	10.64	Pass	Pass

Customer Modification.

- Customer can adjust the ratio as needed: add more additive or add additional water to material if material becomes too fast to dry to be able to perform as weather may influence surface. Typically, with overcast weather the full dosage is necessary.

Surface temperatures are recommended to be 55F and rising for application.

CLEAN-UP: While wet, clean tools with warm water and soap. If dry, scrub with citrus based cleaner or mineral spirits.

WARNING! HARMFUL OR FATAL IF SWALLOWED. FOR EXTERIOR USE ONLY. KEEP OUT OF REACH OF CHILDREN.

WARRANTY AND DISCLAIMER: This product is believed to be of good quality and to be in accordance with the specifications set forth herein. If the product proves to be defective, it shall be replaced at the cost of Advantage. Such replacement is and shall be the only liability of Advantage. Advantage is not liable for product failure where poor drainage and ponding water exist. Advantage shall not be responsible to the consumer or any person for labor costs of any kind or any other costs or damages associated with the product or its installation, application or reapplication or any damages resulting therefrom. This warranty is exclusive and there are no other warranties either expressed or implied, including warranties of fitness or merchantability. No other written or oral representation by any person, entity, dealer, installer or representative of Advantage shall have any force or effect. For additional warranty and disclaimer information, contact the Advantage corporate office at www.AdvantageSealing.com.